

CONTENTS

PREFACE	xix
ACRONYMS	xxiii
1 INTRODUCTION TO MICROWAVE LOS LINK SYSTEMS	1
1.1 Introduction / 1	
1.2 Historic Evolution of Radio Links / 3	
1.3 Point-to-Point Fixed Communication Technologies / 5	
1.3.1 Cabled Transport Systems / 6	
1.3.1.1 <i>xDSL Technologies / 6</i>	
1.3.1.2 <i>Fiber-Optic Links / 8</i>	
1.3.2 Satellite Communication Links / 9	
1.3.3 Other Fixed Wireless Systems / 11	
1.3.3.1 <i>Free Space Optic Links / 11</i>	
1.3.3.2 <i>Wireless Point-to-Multipoint Systems / 12</i>	
1.3.3.3 <i>High-Frequency Links / 13</i>	
1.3.3.4 <i>High-Altitude Platform Stations (HAPS) / 13</i>	
1.4 Field of Application and Use Cases / 13	
1.4.1 Backhaul Networks / 14	
1.4.2 Backhaul in Mobile Networks / 14	
1.4.3 Metro and Edge Networks / 16	
1.4.4 Fixed Access Networks / 17	
1.4.5 Additional Use Cases / 17	

viii CONTENTS

1.5	Basic Structure of a Fixed Service Microwave Link /	18
1.6	Spectrum Management Aspects /	21
1.6.1	ITU-R Radio Regulations: Spectrum Parameters and Definitions /	22
1.6.2	Frequency Allocations /	24
1.7	First Approach to the Design of a Microwave LOS Link /	26
1.8	Link Budget Basics /	28
1.8.1	Link Budget /	28
1.8.1.1	Power Levels /	29
1.8.1.2	Gain and Losses /	29
1.8.1.3	Link Budget Expression /	31
1.8.2	Propagation Losses /	31
1.8.3	Threshold Values and Gross Fade Margin /	33
1.9	Noise /	36
1.10	Interferences /	39
	Bibliography /	40

2 LOSS AND FADING ASSOCIATED WITH TROPOSPHERE PROPAGATION PHENOMENA

42

2.1	Introduction /	42
2.2	Influence of Refraction on Propagation in the Troposphere /	43
2.2.1	Refractive Index and Radio Refractivity N /	46
2.2.2	Radio Refractivity Gradient /	47
2.2.2.1	Variation with Height /	47
2.2.3	Subrefraction Conditions /	48
2.2.4	Super-Refraction Conditions /	48
2.2.5	Ray Bending: Effective Earth Radius /	51
2.2.6	Ducts /	54
2.2.7	Beam Spreading /	56
2.2.8	Variation in the Angles of Launch and Arrival /	57
2.2.9	Troposphere Multipath Propagation /	57
2.2.10	Scintillation /	59
2.3	Terrain Diffraction Losses: Fresnel Zones /	59
2.4	Vegetation Attenuation /	60
2.5	Atmospheric Gas and Vapor Absorption /	61
2.6	Hydrometeors /	62
2.6.1	Absorption Due to Hydrometeors /	63
2.6.2	Cross-Polarization: Coupling Losses /	64
2.7	Reflection /	65

2.8	Distortion due to Propagation Effects / 67
2.8.1	Channel Impulse Response / 67
2.8.2	Two-Ray Model: Frequency Response / 68
	Bibliography / 70

3 FREQUENCY PLAN FOR A FIXED SERVICE MICROWAVE LINK 72

3.1	Frequency Planning Overview / 72
3.2	Bandwidth and Capacity of a Microwave LOS Link / 74
3.2.1	Gross and Net Bit Rate / 75
3.2.2	Spectrum Efficiency / 76
3.2.3	Spectrum Resources / 77
3.3	ITU-R Frequency Plans / 79
3.3.1	General Description of a Radio-Frequency Channel Arrangement Plan / 83
3.3.2	Radio Channel Arrangement Options / 85
3.3.2.1	<i>Alternated Radio Channel Arrangements / 85</i>
3.3.2.2	<i>Radio Channel Arrangements for Co-Channel Band Reuse / 86</i>
3.3.2.3	<i>Radio Channel Arrangements for Interleaved Band Reuse / 87</i>
3.3.3	Radio-Frequency Channel Arrangement Plan: A Detailed Example / 88
3.3.3.1	<i>40 MHz Alternated Radio Channel Arrangement / 88</i>
3.3.3.2	<i>20 MHz Alternated Radio Channel Arrangement / 90</i>
3.3.3.3	<i>30 MHz Radio Channel Arrangement / 91</i>
3.3.3.4	<i>10 MHz Radio Channel Arrangement / 92</i>
3.3.3.5	<i>5 MHz Radio Channel Arrangement / 92</i>
3.3.3.6	<i>Co-Polar Channel Arrangements with Multicarrier Transmission / 92</i>
3.4	Assignment of Radio-frequency Channels / 93
3.4.1	Assignment of Half Bands to Stations / 93
3.4.1.1	<i>Linear Topology / 93</i>
3.4.1.2	<i>Ring Topology / 94</i>
3.4.2	Two Frequency Assignment Plan / 95
3.4.3	Assignment Plan Using More Than Two Frequencies / 97
3.5	Comments on the Frequency Band Choice / 97
	Bibliography / 99

x CONTENTS

4	EQUIPMENT AND SUBSYSTEM TECHNOLOGY ASPECTS: A RADIO LINK DESIGNER APPROACH	100
4.1	Introduction / 100	
4.2	Basic Block Diagrams / 102	
4.2.1	Terminal Stations / 102	
4.2.2	Repeater Stations / 105	
4.3	Transport Technologies / 107	
4.3.1	Plesiochronous Digital Hierarchy PDH / 108	
4.3.2	SONET/SDH Synchronous Networks / 109	
4.3.3	ATM Asynchronous Transfer Mode / 111	
4.3.4	Ethernet / 112	
4.3.5	Synchronization in Hybrid TDM/Ethernet Networks / 113	
4.4	Baseband Unit / 114	
4.4.1	Digital Interfaces / 115	
4.4.2	TDM Radio / 116	
4.4.2.1	Aggregated Radio Frame Structure / 117	
4.4.2.2	Coding and Error Correction / 117	
4.4.2.3	BaseBand Processing / 118	
4.4.3	Ethernet Radio / 119	
4.4.4	Hybrid Radio / 120	
4.4.5	Channel Filtering / 121	
4.5	Modulation and Demodulation / 123	
4.5.1	Modulator and Demodulator Performance / 125	
4.5.2	Examples of Modulation Schemes / 128	
4.5.2.1	Phase Shift Keying 4-PSK / 128	
4.5.2.2	16 Level Quadrature Amplitude Modulation (16-QAM) / 129	
4.5.2.3	M level Quadrature Amplitude Modulation (M-QAM) / 130	
4.5.2.4	Coded Modulation / 131	
4.5.3	Adaptive Modulation / 132	
4.5.4	Error Probability / 134	
4.5.5	Adaptive Equalization / 137	
4.5.5.1	Frequency Domain Equalization / 137	
4.5.5.2	Time Domain Equalization / 138	
4.5.6	Cross-Polar Interference Canceler / 138	
4.6	Transceiver Unit / 139	
4.6.1	Frequency Converter / 139	
4.6.2	Transmitter Power Amplifier / 140	

4.6.3	Receiver RF Low Noise Amplifier /	141
4.6.4	Receiver IF Amplifier /	141
4.6.5	Microwave Circuit Integration /	142
4.7	Antenna Coupling Elements /	142
4.7.1	RF Transmission Lines /	143
4.7.1.1	<i>Coaxial Cables</i> /	143
4.7.1.2	<i>Wave Guides</i> /	144
4.7.2	Branching Circuits /	145
4.7.2.1	<i>Filters</i> /	145
4.7.2.2	<i>Circulators</i> /	145
4.7.2.3	<i>RF Isolators</i> /	145
4.7.2.4	<i>Duplexers</i> /	146
4.7.3	Transmission Line Selection Criteria /	146
4.8	Antennas /	147
4.8.1	Parameters of Parabolic Reflectors /	148
4.8.2	Antenna Gain /	149
4.8.2.1	<i>Directivity</i> /	149
4.8.2.2	<i>Gain</i> /	150
4.8.2.3	<i>Aperture Efficiency</i> /	150
4.8.2.4	<i>Equivalent Isotropically Radiated Power (E.I.R.P.)</i> /	151
4.8.3	Radiation Pattern /	152
4.8.3.1	<i>Beamwidth</i> /	156
4.8.3.2	<i>Minor or Secondary Lobes</i> /	157
4.8.3.3	<i>Field Regions</i> /	157
4.8.4	Mismatch, VSWR and Returning Losses /	157
4.8.5	Polarization /	159
4.8.6	Parabolic Antenna Types /	161
4.8.6.1	<i>Grid Antennas</i> /	161
4.8.6.2	<i>Standard Antennas</i> /	161
4.8.6.3	<i>Focal Plane Antenna</i> /	161
4.8.6.4	<i>Shielded Antenna</i> /	162
4.8.6.5	<i>High Performance Antennas</i> /	162
4.8.7	Microwave Antenna Selection Criteria /	163
4.8.7.1	<i>Operating Frequency Band and Size</i> /	163
4.8.7.2	<i>Gain</i> /	163
4.8.7.3	<i>Radiation Patterns</i> /	163
4.8.7.4	<i>Polarization</i> /	164
4.8.7.5	<i>VSWR</i> /	164

xii CONTENTS

4.8.7.6	<i>Tower Loading and Environmental Considerations</i>	/ 165
4.9	Redundancy Arrangements	/ 166
4.9.1	Unprotected Configurations	/ 168
4.9.2	Hot Standby Configuration	/ 168
4.9.3	Frequency Diversity Configuration	/ 169
4.9.4	2 + 0 Protection with Radio-Link Bonding	/ 169
4.9.5	MIMO Configurations	/ 170
4.10	System Monitoring and Management	/ 171
	Bibliography	/ 172
5	PERFORMANCE OBJECTIVES AND CRITERIA FOR FIXED SERVICE MICROWAVE LINKS	174
5.1	Introduction	/ 174
5.2	Error Performance Objectives and Criteria Based on Recommendation ITU-T G.821	/ 176
5.2.1	Application Scope of Related Recommendations	/ 176
5.2.2	Error Performance and Associated Definitions	/ 176
5.2.2.1	<i>Error Performance Events</i>	/ 176
5.2.2.2	<i>Error Performance Parameters</i>	/ 177
5.2.3	Reference Transmission Models for Performance Objective Allocation	/ 178
5.2.4	Objectives and End-to-End Error Performance Allocation in Real Links	/ 178
5.3	Error Performance Objectives and Criteria Based on Recommendations ITU-T G.826 and ITU-T G.828	/ 179
5.3.1	Application Scope	/ 179
5.3.2	Error Performance and Associated Definitions	/ 180
5.3.2.1	<i>Error Performance Events for Connections (HRX Model)</i>	/ 181
5.3.2.2	<i>Error Performance Events for Paths (HRDP Model)</i>	/ 182
5.3.2.3	<i>Error Performance Parameters</i>	/ 182
5.3.3	Reference Transmission Models for Performance Objective Allocation	/ 182
5.3.4	Objectives and End-to-End Error Performance Allocations in Real Links	/ 184
5.3.4.1	<i>Links in the International Portion</i>	/ 186
5.3.4.2	<i>Links in the National Portion</i>	/ 187

5.4	Availability Criteria / 188
5.4.1	Availability Criteria for Unidirectional Systems / 188
5.4.2	Criteria for Bidirectional Paths/Connections / 188
5.4.3	Availability Parameters / 189
5.5	Availability Objectives for Microwave LOS Links Designed Before 2005 / 190
5.5.1	Basic Concepts and Definitions / 190
5.5.2	Availability Objectives in Real Links / 191
5.6	Availability Objectives for Microwave LOS Links Designed After 2005 / 192
5.6.1	Recommendations and Application Scope / 192
5.6.2	Reference Models for Availability Objective Allocation / 192
5.6.3	Error Performance Concepts Related to Availability / 193
5.6.4	Availability Objectives in Real Microwave LOS Links / 193
5.7	ITU Error Performance and Availability Usage Guidelines / 194
5.8	Degradation due to Interferences / 195
	Bibliography / 196
	Appendix I: Tables for Error Performance Objective Calculations. Recommendation ITU-R F.1668 / 198
	Appendix II: Tables for Availability Objective Calculations. Recommendation ITU-R F.1703 / 201
	Appendix III: Case Studies for Error Performance Objective Calculations. Recommendation ITU-R F.1668 / 202
	Appendix IV: Case Studies for Availability Objective Calculations. Recommendation ITU-R F.1703 / 204

6 LINK PATH ENGINEERING

207

6.1	General Considerations on Link Path Engineering / 207
6.2	Site Selection Criteria / 209
6.3	Digital Terrain Databases / 211
6.4	Profile Extraction, Clearance, and Obstructions / 212
6.5	Optimum Choice of Antenna Heights / 216
6.5.1	Obstacle Clearance Objectives and Criteria / 217
6.5.1.1	<i>Non-diversity Antenna Configurations / 218</i>
6.5.1.2	<i>Two and Three Antenna Space Diversity Configurations / 219</i>
6.5.2	Relevant Reflection Reduction Procedures for Non-diversity Configurations / 221
6.5.2.1	<i>Areas Causing Relevant Reflection / 221</i>

xiv CONTENTS

- 6.5.2.2 *Shielding of the Reflection Point* / 221
- 6.5.2.3 *Translating the Reflection Point* / 222
- 6.5.3 Calculation of Potential Reflection Areas / 222
 - 6.5.3.1 *Geometrical Method* / 222
 - 6.5.3.2 *Analytic Method* / 223

Bibliography / 226

7 PROPAGATION CALCULATION METHODS ACCORDING TO ITU-R P SERIES RECOMMENDATIONS 227

- 7.1 General Considerations on Propagation Calculation Methods / 227
- 7.2 Fading Definition / 228
- 7.3 Reflection on Earth's Surface / 230
 - 7.3.1 Effective Surface Reflection Coefficient / 230
 - 7.3.2 Fading Associated with Specular Reflections / 234
- 7.4 Attenuation Due to Atmospheric Gases / 236
- 7.5 Diffraction Fading / 237
 - 7.5.1 Simplified Calculation from ITU-R Recommendation P.530 / 238
 - 7.5.2 Diffraction on a Knife-Edge / 239
 - 7.5.3 Single Round Shaped Obstacle / 240
 - 7.5.4 Two Isolated Obstacles / 242
 - 7.5.4.1 *Two Obstacles with Similar Clearance* / 243
 - 7.5.4.2 *Two Obstacles with Different Clearance* / 243
 - 7.5.5 Multiple Isolated Obstacles / 245
- 7.6 Multipath Flat Fading / 245
 - 7.6.1 Prediction for Small Percentages of Time / 246
 - 7.6.1.1 *Initial Planning Stage* / 246
 - 7.6.1.2 *Detailed Planning Stage* / 247
 - 7.6.2 Prediction for All Percentages of Time / 248
- 7.7 Distortion Due to Multipath Propagation Effects Under Clear Sky / 250
 - 7.7.1 Signature / 251
 - 7.7.2 Outage Probability Calculation Based on Signatures / 253
- 7.8 Attenuation due to Hydrometeors / 255
 - 7.8.1 Prediction of Attenuation Due to Rain / 255
 - 7.8.1.1 *Specific Attenuation Calculation* / 256
 - 7.8.1.2 *Method for Rain Intensity Excess Value for a Certain Probability Target* / 257
 - 7.8.2 Combined Method for Rain and Wet Snow / 258

7.8.3	Frequency Extrapolation / 260
7.8.4	Polarization Extrapolation / 260
7.8.5	Attenuation Due to Clouds and Fog / 260
7.9	Reduction of Cross-Polar Discrimination (XPD) / 262
7.9.1	XPD Outage Under Clear-Air Conditions / 262
7.9.2	XPD Outage Caused by Rain / 264
7.10	ITU-R Databases for Tropospheric Propagation Studies / 265
	Bibliography / 266
	Appendix I: Data for Specific Attenuation Calculation γ_R / 266
	Appendix II: Data for Calculating Attenuation Due to Wet Snow / 270

8 LINK ENGINEERING ACCORDING TO AVAILABILITY AND ERROR PERFORMANCE CRITERIA 271

8.1	Introduction / 271
8.2	Design According to Availability and Error Performance / 272
8.2.1	Initial Specifications / 272
8.2.2	Microwave LOS Link Design Diagram / 273
8.2.3	Error Performance and Availability Objectives / 274
8.2.3.1	<i>Availability and Bit Error Rate / 274</i>
8.2.3.2	<i>Error Performance Criteria and Bit Error Rate / 275</i>
8.2.4	Link Budget and Thresholds / 276
8.2.5	Impact of Propagation on Availability and Error Performance Calculations / 278
8.3	Microwave LOS Link Design According to Availability Criteria / 281
8.3.1	General / 281
8.3.2	Unavailability Caused by Rain / 282
8.3.3	Rain Attenuation in Multiple Hop Links / 283
8.3.4	Equipment Reliability and Unavailability / 284
8.4	Microwave LOS Link Design According to Error Performance Objectives / 285
8.4.1	General / 285
8.4.2	Design for Operation in Flat Fading Conditions / 286
8.4.2.1	<i>Error Performance and Flat Fading Caused by Refraction / 287</i>
8.4.2.2	<i>Error Performance and Rain / 289</i>
8.4.3	Error Performance and Selective Fading Due to Multipath / 290
8.4.3.1	<i>Net-Fade Margin Method / 291</i>
8.4.4	Occurrence of Simultaneous Fading on Multihop Links / 292

xvi CONTENTS

8.4.5	Cross-Polar Discrimination (XPD) Reduction Outages /	293
8.4.6	Overall Error Performance /	293
8.5	Design in Problematic Propagation Environments /	294
8.5.1	Diversity Techniques /	294
8.5.1.1	<i>Space Diversity</i> /	295
8.5.1.2	<i>Angle Diversity</i> /	297
8.5.1.3	<i>Frequency Diversity</i> /	299
8.5.1.4	<i>Combined Diversity: Space and Frequency</i> /	301
8.5.2	Adaptive Channel Equalization /	303
8.5.3	Adaptive Equalization Combined with Spatial Diversity /	303
8.5.4	Considerations on System Design in the Presence of Ducts /	304
8.6	Quality and Availability Calculation Guidelines in Real Links /	304
8.6.1	Availability /	304
8.6.2	Error Performance /	305
8.7	Interferences /	306
8.7.1	Interferences in the Link Design Process /	306
8.7.2	Reference C/I Values and Threshold Degradation /	308
8.7.3	Interference Propagation /	308
8.7.4	Carrier to Interference (C/I) Calculation Model /	309
8.7.4.1	<i>Multiple Interferences</i> /	312
8.7.4.2	<i>Common Interference Situations</i> /	312
8.7.5	Interference Calculations in Dense Frequency Reuse Scenarios /	315
8.8	Link Engineering Summary Procedure /	319
	Bibliography /	319

9 LINK OPERATION AND MONITORING

321

9.1	Introduction /	321
9.2	Reference Performance Objectives (RPO) /	322
9.3	Bringing into Service (BIS) /	325
9.3.1	BIS Performance Objective Values Calculation Procedure /	325
9.3.2	BIS Test and Evaluation Procedure /	325
9.4	Maintenance /	328
9.4.1	Calculation Method for Maintenance Performance Limits (MPL) /	329
9.4.2	Maintenance Procedures /	330
9.4.2.1	<i>TI Threshold Supervision</i> /	330

CONTENTS **xvii**

9.4.2.2	<i>T2 Threshold Supervision / 331</i>
9.4.2.3	<i>T3 Threshold Supervision / 331</i>
9.4.2.4	<i>Long-Term Measurement and Monitoring / 331</i>
9.4.3	Availability / 331
9.4.4	Evaluation of Error Performance Parameters / 332
9.4.5	Fault Location Procedures / 332
9.4.5.1	<i>Fault Location in pre-ISM Environments / 332</i>
9.4.5.2	<i>Fault Location in ISM Environments / 333</i>
	Bibliography / 333

APPENDIX	335
-----------------	------------

INDEX	378
--------------	------------

