

## On the Achievable Rate of Stationary Fading Channels

Bearbeitet von  
Meik Dörpinghaus

1. Auflage 2011. Buch. XIV, 307 S. Hardcover

ISBN 978 3 642 19779 6

Format (B x L): 15,5 x 23,5 cm

Gewicht: 648 g

[Weitere Fachgebiete > Technik > Nachrichten- und Kommunikationstechnik](#)

Zu [Leseprobe](#)

schnell und portofrei erhältlich bei

The logo for beck-shop.de features the text "beck-shop.de" in a bold, red, sans-serif font. Above the "i" in "shop" are three red dots of increasing size. Below the main text, the words "DIE FACHBUCHHANDLUNG" are written in a smaller, red, all-caps, sans-serif font.

**beck-shop.de**  
DIE FACHBUCHHANDLUNG

Die Online-Fachbuchhandlung [beck-shop.de](#) ist spezialisiert auf Fachbücher, insbesondere Recht, Steuern und Wirtschaft. Im Sortiment finden Sie alle Medien (Bücher, Zeitschriften, CDs, eBooks, etc.) aller Verlage. Ergänzt wird das Programm durch Services wie Neuerscheinungsdienst oder Zusammenstellungen von Büchern zu Sonderpreisen. Der Shop führt mehr als 8 Millionen Produkte.

# Contents

|          |                                                                    |    |
|----------|--------------------------------------------------------------------|----|
| <b>1</b> | <b>Introduction</b>                                                | 1  |
| 1.1      | Prior Work                                                         | 4  |
| 1.2      | Objectives and Contributions                                       | 6  |
| 1.3      | Outline                                                            | 13 |
| <b>2</b> | <b>Discrete-Time Flat-Fading System Model</b>                      | 15 |
| 2.1      | Rayleigh Fading and Jakes' Model                                   | 17 |
| 2.2      | Matrix-Vector Notation                                             | 19 |
| 2.3      | Limitations of the Model                                           | 20 |
| 2.4      | Operational and Information Theoretic Capacity                     | 22 |
| 2.4.1    | Outage Capacity                                                    | 25 |
| <b>3</b> | <b>Bounds on the Achievable Rate of a Flat-Fading Channel</b>      | 27 |
| 3.1      | The Mutual Information Rate $\mathcal{I}'(\mathbf{y}; \mathbf{x})$ | 28 |
| 3.2      | The Received Signal Entropy Rate $h'(\mathbf{y})$                  | 29 |
| 3.2.1    | Lower Bound on $h'(\mathbf{y})$                                    | 30 |
| 3.2.2    | Upper Bound on $h'(\mathbf{y})$                                    | 30 |
| 3.3      | The Entropy Rate $h'(\mathbf{y} \mathbf{x})$                       | 31 |
| 3.3.1    | Upper Bound on $h'(\mathbf{y} \mathbf{x})$                         | 31 |
| 3.3.2    | Lower Bound on $h'(\mathbf{y} \mathbf{x})$ for a Rectangular PSD   | 33 |
| 3.4      | The Achievable Rate                                                | 40 |
| 3.4.1    | Upper Bound                                                        | 40 |
| 3.4.2    | Lower Bound                                                        | 47 |
| 3.4.3    | Tightness of Bounds on the Achievable Rate                         | 49 |
| 3.4.4    | The Asymptotic High SNR Behavior                                   | 53 |
| 3.5      | Comparison to Asymptotes in [67]                                   | 55 |
| 3.6      | Comparison to Bounds in [105] and [107]                            | 56 |
| 3.7      | Summary                                                            | 59 |

|          |                                                                                                                                                                  |     |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| <b>4</b> | <b>Bounds on the Achievable Rate of a Flat-Fading Channel Based on Prediction</b>                                                                                | 61  |
| 4.1      | Calculation of $h'(\mathbf{y} \mathbf{x})$ based on Channel Prediction                                                                                           | 63  |
| 4.2      | Upper Bound on $h'(\mathbf{y})$                                                                                                                                  | 65  |
| 4.2.1    | Simple Upper Bound on $h'(\mathbf{y})$                                                                                                                           | 66  |
| 4.2.2    | Ideas for an Enhanced Upper Bound on $h'(\mathbf{y})$                                                                                                            | 66  |
| 4.3      | Upper Bound on the Achievable Rate                                                                                                                               | 70  |
| 4.3.1    | The Prediction Error Variance                                                                                                                                    | 71  |
| 4.3.2    | Effect of Constraints on the Input Distribution                                                                                                                  | 74  |
| 4.4      | Comparison to Bounds given in Chapter 3                                                                                                                          | 76  |
| 4.4.1    | Numerical Evaluation                                                                                                                                             | 76  |
| 4.4.2    | Relation of Bounds on $h'(\mathbf{y} \mathbf{x})$                                                                                                                | 79  |
| 4.5      | Summary                                                                                                                                                          | 80  |
| <b>5</b> | <b>Pilot Based Synchronized Detection</b>                                                                                                                        | 81  |
| 5.1      | Synchronized Detection                                                                                                                                           | 81  |
| 5.1.1    | Channel Estimation                                                                                                                                               | 83  |
| 5.1.2    | Interleaving and Detection/Decoding                                                                                                                              | 86  |
| 5.2      | Achievable Rate                                                                                                                                                  | 90  |
| 5.2.1    | Comparison to the Achievable Rate with i.i.d. Gaussian Inputs                                                                                                    | 95  |
| 5.2.2    | Optimized Pilot-to-Data Power Ratio                                                                                                                              | 96  |
| 5.3      | Summary                                                                                                                                                          | 99  |
| <b>6</b> | <b>Iterative Code-Aided Synchronized Detection</b>                                                                                                               | 101 |
| 6.1      | Principle of Iterative Code-Aided Synchronized Detection                                                                                                         | 102 |
| 6.1.1    | Modified Channel Estimation Unit                                                                                                                                 | 108 |
| 6.2      | Achievable Rate with Iterative Code-Aided Synchronized Detection                                                                                                 | 109 |
| 6.2.1    | Upper-Bounding Approach on the Achievable Rate                                                                                                                   | 110 |
| 6.2.2    | The Channel Interpolation Separation Inequality                                                                                                                  | 113 |
| 6.2.3    | The Term $\mathcal{I}(y_0; x_0 \mathbf{y}_{\setminus 0}, \mathbf{x}_{\setminus 0})$                                                                              | 115 |
| 6.2.4    | The Term $\mathcal{I}(y_0; \mathbf{x}_{\setminus 0} \mathbf{y}_{\setminus 0})$                                                                                   | 118 |
| 6.2.5    | An Upper Bound on $\mathcal{I}(x_0; y_0 \hat{h}_0, \mathbf{x}_{\setminus 0})$                                                                                    | 121 |
| 6.2.6    | Approximative Upper Bound on the Achievable Rate with the Iterative Code-Aided Synchronized Detection based Receiver using the Modified Channel Estimator (6.19) | 129 |
| 6.2.7    | Numerical Evaluation                                                                                                                                             | 130 |
| 6.3      | Summary                                                                                                                                                          | 133 |
| <b>7</b> | <b>Joint Processing of Pilot and Data Symbols</b>                                                                                                                | 137 |
| 7.1      | System Model                                                                                                                                                     | 138 |
| 7.2      | Expressing $\mathcal{I}(\mathbf{y}; \mathbf{x})$ via the Pilot based Channel Estimate $\hat{\mathbf{h}}_{\text{pil}}$                                            | 138 |
| 7.3      | Lower Bound on the Achievable Rate with Joint Processing                                                                                                         | 141 |

|           |                                                                     |            |
|-----------|---------------------------------------------------------------------|------------|
| 7.3.1     | Fixed Pilot Spacing                                                 | 146        |
| 7.3.2     | Optimal Pilot Spacing                                               | 146        |
| 7.4       | Numerical Evaluation                                                | 147        |
| 7.5       | Summary                                                             | 151        |
| <b>8</b>  | <b>MIMO Flat-Fading Channels</b>                                    | <b>153</b> |
| 8.1       | MIMO System Model                                                   | 154        |
| 8.1.1     | Spatially Uncorrelated Channel                                      | 156        |
| 8.1.2     | Spatial Antenna Correlation                                         | 157        |
| 8.2       | Bounds on the Achievable Rate                                       | 159        |
| 8.2.1     | The Received Signal Entropy Rate $h'(\mathbf{y})$                   | 161        |
| 8.2.2     | The Entropy Rate $h'(\mathbf{y} \mathbf{x})$                        | 162        |
| 8.2.3     | The Achievable Rate                                                 | 166        |
| 8.3       | Comparison with Pilot Based Synchronized Detection                  | 180        |
| 8.3.1     | Achievable Rate                                                     | 182        |
| 8.4       | Summary                                                             | 188        |
| <b>9</b>  | <b>Frequency-Selective Channels</b>                                 | <b>189</b> |
| 9.1       | Channel Model                                                       | 190        |
| 9.1.1     | Stochastic Characterization                                         | 191        |
| 9.1.2     | The Underspread Assumption                                          | 191        |
| 9.1.3     | Discrete-Time Discrete-Frequency Input-Output<br>Relation           | 194        |
| 9.2       | Bounds on the Achievable Rate                                       | 197        |
| 9.2.1     | The Channel Output Entropy Rate $h'(\mathbf{y})$                    | 198        |
| 9.2.2     | The Entropy Rate $h'(\mathbf{y} \mathbf{x})$                        | 199        |
| 9.2.3     | The Achievable Rate                                                 | 204        |
| 9.3       | Comparison with Pilot Based Synchronized Detection                  | 215        |
| 9.3.1     | Channel Estimation                                                  | 217        |
| 9.3.2     | Achievable Rate                                                     | 219        |
| 9.4       | Summary                                                             | 224        |
| <b>10</b> | <b>Optimum Discrete Signaling</b>                                   | <b>225</b> |
| 10.1      | Capacity of a Discrete Input Time-Selective Block Fading<br>Channel | 227        |
| 10.1.1    | Optimum Discrete Input Distributions                                | 229        |
| 10.2      | Constant Modulus Input Distributions                                | 232        |
| 10.2.1    | Distinguishable Transmit Sequences                                  | 233        |
| 10.2.2    | Optimum Input Distribution                                          | 233        |
| 10.2.3    | Asymptotic SNR Behavior                                             | 235        |
| 10.2.4    | Interpretation                                                      | 236        |
| 10.2.5    | Numerical Results                                                   | 237        |
| 10.3      | What about Periodic Pilot Symbols in Stationary Fading?             | 238        |
| 10.4      | Conclusion                                                          | 240        |
| <b>11</b> | <b>Conclusion</b>                                                   | <b>243</b> |

|          |                                                                                                                           |     |
|----------|---------------------------------------------------------------------------------------------------------------------------|-----|
| <b>A</b> | <b>Mathematical Derivations and Proofs</b> . . . . .                                                                      | 251 |
| A.1      | Modified Upper Bound on $h'(\mathbf{y})$ for PG Inputs . . . . .                                                          | 251 |
| A.2      | Calculation of Sufficient Conditions for $\alpha_{\text{opt}} = 1$ in (3.76) . . . . .                                    | 253 |
| A.3      | Proof of Monotonicity of $\Delta_{h'(\mathbf{y})}$ . . . . .                                                              | 254 |
| A.4      | Calculation of $E[\varepsilon_{\text{pred}}]$ for the Enhanced Upper Bound on $h'(\mathbf{y})$ . . . . .                  | 256 |
| A.5      | Proof of Convexity of (4.49) . . . . .                                                                                    | 260 |
| A.6      | One-Step Prediction Error Variance . . . . .                                                                              | 263 |
| A.7      | Proof of Equivalency of (5.1) and (5.5) for CM input symbols . . . . .                                                    | 265 |
| A.8      | Proof of Monotonicity of (6.58) . . . . .                                                                                 | 266 |
| A.9      | Proof of Inequality (A.75) . . . . .                                                                                      | 269 |
| A.10     | Comparison of Interpolation and Prediction Error Variance . . . . .                                                       | 270 |
| A.11     | Proof for Minimization of $h'(\mathbf{e}_{\text{joint}} \mathbf{x}_D, \mathbf{x}_P)$ in (7.23) by CM Modulation . . . . . | 271 |
| A.12     | Estimation Error Spectra $S_{e_{\text{pil}}}(f)$ and $S_{e_{\text{joint,CM}}}(f)$ . . . . .                               | 278 |
| A.13     | Proof of Inequality (9.53) . . . . .                                                                                      | 281 |
|          | <b>Abbreviations</b> . . . . .                                                                                            | 285 |
|          | <b>List of Symbols</b> . . . . .                                                                                          | 287 |
|          | <b>References</b> . . . . .                                                                                               | 295 |
|          | <b>Index</b> . . . . .                                                                                                    | 303 |